


Material	WLT or BLT or WHT or BHT or WSM or SMB	
Belt type	1015	
Width (A)	K.. (in inches)	Belts with flights have minimal width of 6"
Flights	RF3 or RF4 or RH..	Ribbed 3 to 4" high flight or special height in mm
Pitch between flights	T..P	Flight on every .. th row
Flight side-indent	N0 or N1 or N..	Standard 0 or 1"; non-standard increments of 1/2", starting with 1 1/2"

If you need flights, describe the belt by choosing the required options listed in the 2nd column of the table

Classic Sprockets



Sprocket Type	Code Number	Number of Teeth	Bore	Pitch Diameter	Outside Diameter	Hub Width
			B	E	F	A
			mm/inch	mm	mm	mm
Round Bores						
KU 1010 T10 R40	897.10.33	10	40	82.2	82.7	25
KU 1010 T12 R40	897.10.42	12	40	98.1	98.9	
KU 1010 T16 R40	897.10.71	16	40	130.2	131.5	
KU 1010 T18 R40	897.10.86	18	40	146.3	147.8	
KU 1010 T20 R40	897.11.01	20	40	162.4	164.0	
Square Bores						
KU 1010 T10 S40	897.10.35	10	40	82.2	82.7	25
KU 1010 T12 S40	897.10.44	12	40	98.1	98.9	
KU 1010 T16 S40	897.10.73	16	40	130.2	131.5	
KU 1010 T18 S40	897.10.88	18	40	146.3	147.8	
KU 1010 T20 S40	897.11.03	20	40	162.4	164.0	