

UCFN/C - SUCFN/C - HCFN/C - SHCFN/C

dia. d mm	Series	Housing material		e	a	s	Dimensions in mm					Dg	Bore in frame ¹⁾ Df		Bearing	Weight Kg	Spare parts Cover orange								
		Polyamide PA FV Solid Flange (black) Cover (orange)	Polypropylene PP FV Solid Flange (white) Cover (orange)				Code	Code																	
Grub screws shaft locking • Closed unit																									
30	UCFN 206 C	632223	632463	83	110	11	15	20	42	55	62	60	50	Type A	0,50	63154									
35*	SUCFN 207 C	632233	632473	83	110	11	15	19,5	43	59	72	70	55	Type A	0,61	682022									
40*	SUCFN 208 C	632243	632483	83	110	11	15	19	44	66	80	78	65	Type A	0,82	600882									
Grub screws shaft locking • Open unit																									
30	UCFN 206 C	632253	632493	83	110	11	15	20	42	55	62	60	50	Type A	0,50	69965									
35*	SUCFN 207 C	632263	632503	83	110	11	15	19,5	43	59	72	70	55	Type A	0,61	682032									
40*	SUCFN 208 C	632273	632513	83	110	11	15	19	44	66	80	78	65	Type A	0,82	600892									
Eccentric collar shaft locking • Closed unit																									
30	HCFN 206 C	632283	632523	83	110	11	15	20	46,7	55	62	60	50	Type D	0,57	63154									
35*	SHCFN 207 C	632293	632533	83	110	11	15	19,5	48,9	59	72	70	55	Type D	0,79	682022									
40*	SHCFN 208 C	632303	632543	83	110	11	15	19	51,7	66	80	78	65	Type D	1,01	600882									
Eccentric collar shaft locking • Open unit																									
30	HCFN 206 C	632313	632553	83	110	11	15	20	46,7	55	62	60	50	Type D	0,57	69965									
35*	SHCFN 207 C	632323	632563	83	110	11	15	19,5	48,9	59	72	70	55	Type D	0,79	682032									
40*	SHCFN 208 C	632333	632573	83	110	11	15	19	51,7	66	80	78	65	Type D	1,01	600892									

Item code for order = B0000 + Code

*** = Version with special fixing holes.**

¹⁾ = Dimensions Df max / Df min must be respected to ensure positive retention of the seals and to allow air bleeding during lubrication.

Packaging: 6 pieces.