

UCF/C - SUCF/C - HCF/C - SHCF/C

dia. d mm	Series	Housing material		Dimensions in mm										Bore in frame ²⁾ Df		Bearing	Weight Kg	Spare parts	
		Polyamide PA FV Standard Flange (black) Cover (orange)	Polypropylene PP FV Solid Flange (white) Cover (orange)															Cover orange	
		Code	e	a	s	g	i	z	t	Dg	max.	min.	Code						
		Grub screws shaft locking • Closed unit																	
25	UCF 205 C	64573	680932	70	98	11	22,5	16,8	36,3	49,5	52	50	45	Type A	0,40	681952			
25*	SUCF 205 C	603043	-	83	110	11	26	19,3	38,8	54	52	50	45	Type A	0,50	681952			
30	UCF 206 C	63112	680942	83	110	11	26	20	42	56	62	60	50	Type A	0,56	63154			
35	UCF 207 C	64018	680952	92	120	11	26	19,5	43	59	72	70	55	Type A	0,72	682022			
35*	SUCF 207 C	680522 ¹⁾	680962	83	110	11	26	19,5	43	61	72	70	55	Type A	0,67	63539			
40	UCF 208 C	68916	680972	102	131	11	30	22	47	65,5	80	78	65	Type A	0,95	63539			
40*	SUCF 208 C	61819	680982	83	110	11	26	19	44	66	80	78	65	Type A	0,88	600882			
45*	SUCF 209 C	686592 ¹⁾	686752	102	131	11	30	23	54	73	85	83	75	Type A	1,10	686972			
50*	SUCF 210 C	686602 ¹⁾	686762	102	131	11	30	23	55,6	73	90	88	80	Type A	1,20	686972			
Grub screws shaft locking • Open unit																			
25	UCF 205 C	64623	680992	70	98	11	22,5	16,8	36,3	49,5	52	50	45	Type A	0,40	681972			
25*	SUCF 205 C	603053	-	83	110	11	26	19,3	38,8	54	52	50	45	Type A	0,50	681972			
30	UCF 206 C	63172	681002	83	110	11	26	20	42	56	62	60	50	Type A	0,56	69965			
35	UCF 207 C	64028	681012	92	120	11	26	19,5	43	59	72	70	55	Type A	0,72	682032			
35*	SUCF 207 C	680582 ¹⁾	681022	83	110	11	26	19,5	43	61	72	70	55	Type A	0,67	615692			
40	UCF 208 C	68926	681032	102	131	11	30	22	47	65,5	80	78	65	Type A	0,95	63549			
40*	SUCF 208 C	61829	681042	83	110	11	26	19	44	66	80	78	65	Type A	0,88	600892			
45*	SUCF 209 C	686612 ¹⁾	686772	102	131	11	30	23	54	73	85	83	75	Type A	1,10	686992			
50*	SUCF 210 C	686622 ¹⁾	686782	102	131	11	30	23	55,6	73	90	88	80	Type A	1,20	687002			
Eccentric collar shaft locking • Closed unit																			
25	HCF 205 C	680452	681052	70	98	11	22,5	16,8	40,2	49,5	52	50	45	Type D	0,44	681952			
25*	SHCF 205 C	603063	-	83	110	11	26	19,3	42,7	54	52	50	45	Type D	0,57	681952			
30	HCF 206 C	621501	681062	83	110	11	26	20	46,7	56	62	60	50	Type D	0,63	63154			
35	HCF 207 C	680462	681072	92	120	11	26	19,5	48,9	59	72	70	55	Type D	0,90	682022			
35*	SHCF 207 C	680642 ¹⁾	681082	83	110	11	26	19,5	48,9	61	72	70	55	Type D	0,85	63539			
40*	SHCF 208 C	62439	681092	83	110	11	26	19	51,7	66	80	78	65	Type D	1,07	600882			
45*	SHCF 209 C	686632 ¹⁾	686792	102	131	11	30	23	55,7	73	85	83	75	Type D	1,29	686972			
50*	SHCF 210 C	686642	686802	102	131	11	30	23	55,7	73	90	88	80	Type D	1,39	686972			
Eccentric collar shaft locking • Open unit																			
25	HCF 205 C	680472	681102	70	98	11	22,5	16,8	40,2	49,5	52	50	45	Type D	0,44	681972			
25*	SHCF 205 C	603073	-	83	110	11	26	19,3	42,7	54	52	50	45	Type D	0,57	681972			
30	HCF 206 C	621481	681112	83	110	11	26	20	46,7	56	62	60	50	Type D	0,63	69965			
35	HCF 207 C	680482	681122	92	120	11	26	19,5	48,9	59	72	70	55	Type D	0,90	682032			
35*	SHCF 207 C	680692 ¹⁾	681132	83	110	11	26	19,5	48,9	61	72	70	55	Type D	0,85	615692			
40*	SHCF 208 C	62449	681142	83	110	11	26	19	51,7	66	80	78	65	Type D	1,07	600892			
45*	SHCF 209 C	686652 ¹⁾	686812	102	131	11	30	23	55,7	73	85	83	75	Type D	1,29	686992			
50*	SHCF 210 C	686662 ¹⁾	686822	102	131	11	30	23	55,7	73	90	88	80	Type D	1,39	687002			

Item code for order = B0000 + Code

* = Version with special fixing holes.

¹⁾ = Solid flange.

²⁾ = Dimensions Df max / Df min must be respected to ensure positive retention of the seals and to allow air bleeding during lubrication.

Packaging: 6 pieces.

Best Seller

Standard

On request