

Shaft dia. da mm	Bearing dia. d mm	Series	Housing material		e	a	Dimensions in mm						Bore in frame ¹⁾ Df		Bearing	Weight Kg
			Polyamide PA FV Standard Flange (black)	Polypropylene PP FV Standard Flange (black)			s	g	i	h	t	Dg	max.	min.		
			Code													
Closed unit																
30	25	F 1205	64433	681702	70	98	11	22,5	18,5	11	36,5	52	50	47	Type 1200	0,36
35	30	F 1206	65811	681712	83	110	11	26	19	11	40	62	60	52	Type 1200	0,53
40	35	F 1207	63978	681722	92	120	11	26	19,5	11	39,5	72	70	60	Type 1200	0,62
40*	35*	SF 1207	699782	699802	83	110	11	26	19	10	39	72	70	60	Type 1200	0,60
45	40	F 1208	68876	681732	102	131	11	30	24,5	15,5	45	80	78	65	Type 1200	0,85
45*	40*	SF 1208	69988	681742	83	110	11	26	19	10	39	80	78	65	Type 1200	0,78
Open unit																
30	25	F 1205	64483	681752	70	98	11	22,5	18,5	11	36,5	52	50	47	Type 1200	0,36
35	30	F 1206	65901	681762	83	110	11	26	19	11	40	62	60	52	Type 1200	0,53
40	35	F 1207	63988	681772	92	120	11	26	19,5	11	39,5	72	70	60	Type 1200	0,62
40*	35*	SF 1207	699792	699812	83	110	11	26	19	10	39	72	70	60	Type 1200	0,60
45	40	F 1208	68886	681782	102	131	11	30	24,5	15,5	45	80	78	65	Type 1200	0,85
45*	40*	SF 1208	69998	681792	83	110	11	26	19	10	39	80	78	65	Type 1200	0,78

Item code for order = B0000 + Code

*** = Version with special fixing holes.**

¹⁾ = Dimensions Df max / Df min must be respected to ensure positive retention of the seals and to allow air bleeding during lubrication.

Packaging: 6 pieces.