

dia. d mm	Series	Housing material		Dimensions in mm										Bearing	Weight Kg
		Polyamide PA FV Flange (black)	Polypropylene PP FV Flange (white)	e	a	h	b	s1	s2	g	w	i	z		
		Code													
Grub screws shaft locking • Version with bearing Type B															
20	UCP 204	682921	-	96	128	33,3	67	12	10	17	30	18,9	37,2	Type B	0,27
25	UCP 205	648781	-	106	140	36,5	75	12	10	17	34,5	18,8	38,5	Type B	0,33
30	UCP 206	648791	-	121	163	42,9	88	14	10	20	36	19,7	41,9	Type B	0,49
35	UCP 207	648801	-	126	167	47,6	98	14	10	20	38,6	21,3	46,7	Type B	0,64
40	UCP 208	683021	-	136	185	50	102	14	10	20	38,6	25	55,2	Type B	0,84
Grub screws shaft locking • Version with stainless steel bearing Type C															
20	UCP 204	646492	679002	96	128	33,3	67	12	10	17	30	18,9	37,2	Type C	0,27
25	UCP 205	646502	679012	106	140	36,5	75	12	10	17	34,5	18,8	38,6	Type C	0,33
30	UCP 206	646512	679022	121	163	42,9	88	14	10	20	36	19,7	41,9	Type C	0,49
35	UCP 207	646522	679032	126	167	47,6	98	14	10	20	38,6	21,3	46,7	Type C	0,64
40	UCP 208	646532	679042	136	185	50	102	14	10	20	38,6	25	55,2	Type C	0,84
Grub screws shaft locking • Version with bearing Type A															
20	UCP 204	678552	678852	96	128	33,3	67	12	10	17	30	18,9	36,9	Type A	0,24
25	UCP 205	678562	678862	106	140	36,5	75	12	10	17	34,5	18,8	38,3	Type A	0,30
30	UCP 206	678572	678872	121	163	42,9	88	14	10	20	36	19,7	41,7	Type A	0,44
35	UCP 207	678582	678882	126	167	47,6	98	14	10	20	38,6	21,3	44,8	Type A	0,54
40	UCP 208	678592	678892	136	185	50	102	14	10	20	38,6	25	50	Type A	0,72
Eccentric collar shaft locking • Version with bearing Type D															
20	HCP 204	678602	678902	96	128	33,3	67	12	10	17	30	18,9	42,3	Type D	0,29
25	HCP 205	678612	678912	106	140	36,5	75	12	10	17	34,5	18,8	42,2	Type D	0,34
30	HCP 206	678622	678922	121	163	42,9	88	14	10	20	36	19,7	46,4	Type D	0,51
35	HCP 207	678632	678932	126	167	47,6	98	14	10	20	38,6	21,3	50,7	Type D	0,72
40	HCP 208	678642	678942	136	185	50	102	14	10	20	38,6	25	57,7	Type D	0,91

Item code for order = B0000 + Code

Packaging: 6 pieces.