

		Housing material																Bore in frame ¹⁾ Df		Bearing	Weight Kg	Spare parts Cover orange	
dia. d mm	Series	Polyamide PA FV Standard Flange (black) Cover (orange)	Polypropylene PP FV Solid Flange (white) Cover (orange)	Dimensions in mm														max.	min.			Code	
		Code		a	b	c	p	e	f	s	g	i	z	t	Dg								
Grub screws shaft locking • Closed unit																							
20	UCFB 204 C	601133N	601373N	124,2	68,8	89,8	46	41,3	28,6	11	14	16,4	34,4	49	47	45	40	Type A	0,26	681942			
25	UCFB 205 C	656542N	677832N	124,2	68,8	89,8	46	41,3	28,6	11	14	17,8	37,3	52	52	50	45	Type A	0,32	681952			
30	UCFB 206 C	656562	677842	138,6	81,3	97,9	52,4	47,6	31,7	11	14	20	42	55	62	60	50	Type A	0,47	63154			
35	UCFB 207 C	656582	677852	154,5	93,7	107,6	60,3	50,8	31,7	13	15	19,5	43	59	72	70	55	Type A	0,64	682022			
40	UCFB 208 C	601143	601383	164	100	114	60	50	31	13	-	22	47	66,5	80	78	65	Type A	0,84	600882			
Grub screws shaft locking • Open unit																							
20	UCFB 204 C	601153N	601393N	124,2	68,8	89,8	46	41,3	28,6	11	14	16,4	34,4	49	47	45	40	Type A	0,26	681962			
25	UCFB 205 C	656552N	677862N	124,2	68,8	89,8	46	41,3	28,6	11	14	17,8	37,3	52	52	50	45	Type A	0,32	681972			
30	UCFB 206 C	656572	677872	138,6	81,3	97,9	52,4	47,6	31,7	11	14	20	42	55	62	60	50	Type A	0,47	69965			
35	UCFB 207 C	656592	677882	154,5	93,7	107,6	60,3	50,8	31,7	13	15	19,5	43	59	72	70	55	Type A	0,64	682032			
40	UCFB 208 C	601163	601403	164	100	114	60	50	31	13	-	22	47	66,5	80	78	65	Type A	0,84	600892			
Eccentric collar shaft locking • Closed unit																							
20	HCFB 204 C	601173N	601413N	124,2	68,8	89,8	46	41,3	28,6	11	14	16,4	39,8	49	47	45	40	Type D	0,29	681942			
25	HCFB 205 C	663252N	677892N	124,2	68,8	89,8	46	41,3	28,6	11	14	17,8	41,2	57	52	50	45	Type D	0,35	681952			
30	HCFB 206 C	663262	677902	138,6	81,3	97,9	52,4	47,6	31,7	11	14	20	46,7	60	62	60	50	Type D	0,50	63154			
35	HCFB 207 C	663272	677912	154,5	93,7	107,6	60,3	50,8	31,7	13	15	19,5	48,9	64,5	72	70	55	Type D	0,67	682022			
40	HCFB 208 C	601183	601423	164	100	114	60	50	31	13	-	22	54,7	72	80	78	65	Type D	0,92	600882			
Eccentric collar shaft locking • Open unit																							
20	HCFB 204 C	601193N	601433N	124,2	68,8	89,8	46	41,3	28,6	11	14	16,4	39,8	49	47	45	40	Type D	0,29	681962			
25	HCFB 205 C	663282N	677922N	124,2	68,8	89,8	46	41,3	28,6	11	14	17,8	41,2	57	52	50	45	Type D	0,35	681972			
30	HCFB 206 C	663292	677932	138,6	81,3	97,9	52,4	47,6	31,7	11	14	20	46,7	60	62	60	50	Type D	0,50	69965			
35	HCFB 207 C	663302	677942	154,5	93,7	107,6	60,3	50,8	31,7	13	15	19,5	48,9	64,5	72	70	55	Type D	0,67	682032			
40	HCFB 208 C	601203	601443	164	100	114	60	50	31	13	-	22	54,7	72	80	78	65	Type D	0,92	600892			

Item code for order = B0000 + Code
¹⁾ = Dimensions Df max / Df min must be respected to ensure positive retention of the seals and to allow air bleeding during lubrication.

Packaging: 6 pieces.