

UCF/C - SUCF/C - HCF/C - SHCF/C

		Housing material															
dia. d mm	Series	Polyamide PA FV Standard Flange (black) Cover (orange)	Dimensions in mm								Bore in frame ²⁾ Df		Bearing	Weight Kg	Spare parts Cover orange		
		Code	e	a	s	g	i	z	t	Dg	max.	min.			Code		
Grub screws shaft locking • Closed unit																	
25	UCF 205 C	64573	70	98	11	22,5	16,8	36,3	49,5	52	50	45	Type A	0,40	681952		
30	UCF 206 C	63112	83	110	11	26	20	42	56	62	60	50	Type A	0,56	63154		
35	UCF 207 C	64018	92	120	11	26	19,5	43	59	72	70	55	Type A	0,72	682022		
35*	SUCF 207 C	680522 ¹⁾	83	110	11	26	19,5	43	61	72	70	55	Type A	0,67	63539		
40	UCF 208 C	68916	102	131	11	30	22	47	65,5	80	78	65	Type A	0,95	63539		
40*	SUCF 208 C	61819	83	110	11	26	19	44	66	80	78	65	Type A	0,88	600882		
Grub screws shaft locking • Open unit																	
25	UCF 205 C	64623	70	98	11	22,5	16,8	36,3	49,5	52	50	45	Type A	0,40	681972		
30	UCF 206 C	63172	83	110	11	26	20	42	56	62	60	50	Type A	0,56	69965		
35	UCF 207 C	64028	92	120	11	26	19,5	43	59	72	70	55	Type A	0,72	682032		
35*	SUCF 207 C	680582 ¹⁾	83	110	11	26	19,5	43	61	72	70	55	Type A	0,67	615692		
40	UCF 208 C	68926	102	131	11	30	22	47	65,5	80	78	65	Type A	0,95	63549		
40*	SUCF 208 C	61829	83	110	11	26	19	44	66	80	78	65	Type A	0,88	600892		
Eccentric collar shaft locking • Closed unit																	
40*	SHCF 208 C	62439	83	110	11	26	19	51,7	66	80	78	65	Type D	1,07	600882		
Eccentric collar shaft locking • Open unit																	
40*	SHCF 208 C	62449	83	110	11	26	19	51,7	66	80	78	65	Type D	1,07	600892		

* = Version with special fixing holes.

¹⁾ = Solid flange.

²⁾ = Dimensions Df max / Df min must be respected to ensure positive retention of the seals and to allow air bleeding during lubrication.

Packaging: 4 pieces.