

UCF - SUCF - HCF - SHCF

dia. d mm	Series	Housing material										Bore in frame Df mm	Bearing	Weight Kg
		Polyamide PA FV Standard Flange (black)	Dimensions in mm											
			Code	e	a	s	g	i	h	l	z			
Grub screws shaft locking • Version with bearing Type B														
25	UCF 205	64533	70	98	11	22,5	16,8	14,3	27,5	36,5	29	Type B	0,44	
30	UCF 206	60722	83	110	11	26	20	15,9	32,5	42,2	34	Type B	0,57	
35	UCF 207	64058	92	120	11	26	19,5	17,5	32	44,9	39	Type B	0,72	
Grub screws shaft locking • Version with stainless steel bearing Type C														
25	UCF 205	646592	70	98	11	22,5	16,8	14,3	27,5	36,6	29	Type C	0,44	
30	UCF 206	646602	83	110	11	26	20	15,9	32,5	42,2	34	Type C	0,57	
Grub screws shaft locking • Version with bearing Type A														
25	UCF 205	656752	70	98	11	22,5	16,8	-	27,5	36,3	29	Type A	0,39	
30	UCF 206	666442	83	110	11	26	20	-	32,5	42	34	Type A	0,54	
35	UCF 207	666452	92	120	11	26	19,5	-	32	43	39	Type A	0,69	
40	UCF 208	666462	102	131	11	30	22	-	36	47	44	Type A	0,92	
40*	SUCF 208	681552	83	110	11	26	19	-	36	44	44	Type A	0,85	
Eccentric collar shaft locking • Version with bearing Type D														
40*	SHCF 208	62349	83	110	11	26	19	-	36	51,7	44	Type D	1,04	

Item code for order = B0000 + Code

*** = Version with special fixing holes.**

¹⁾ = Solid flange.

• = Solid flange 19,5.

Packaging: 4 pieces.