

# UCFS/C - SUCFS/C - HCFS/C - SHCFS/C

|                                              |             | Housing material                                                                                               |    |     |      |      |    |      |      |    |      |      |         | Bore in frame <sup>1)</sup><br>Df |        | Spare parts<br>Cover orange |  |
|----------------------------------------------|-------------|----------------------------------------------------------------------------------------------------------------|----|-----|------|------|----|------|------|----|------|------|---------|-----------------------------------|--------|-----------------------------|--|
| dia.<br>d<br>mm                              | Series      | Polyamide<br>PA FV with austenitic<br>stainless steel<br>surface<br>Solid Flange<br>Cover (orange)<br><br>Code | e  | a   | s    | g    | i  | z    | t    | Dg | max. | min. | Bearing | Weight<br>Kg                      | Code   |                             |  |
| Grub screws shaft locking • Closed unit      |             |                                                                                                                |    |     |      |      |    |      |      |    |      |      |         |                                   |        |                             |  |
| 30                                           | UCFS 206 C  | 647613                                                                                                         | 83 | 111 | 10,5 | 15,9 | 22 | 44   | 65,8 | 62 | 60   | 50   | Type A  | 0,73                              | 63539  |                             |  |
| 35*                                          | SUCFS 207 C | 647623                                                                                                         | 83 | 111 | 10,5 | 15,9 | 22 | 45,5 | 65,8 | 72 | 70   | 55   | Type A  | 0,84                              | 63539  |                             |  |
| 40*                                          | SUCFS 208 C | 647633                                                                                                         | 83 | 111 | 10,5 | 15,9 | 22 | 47   | 65,8 | 80 | 78   | 65   | Type A  | 0,94                              | 63539  |                             |  |
| Grub screws shaft locking • Open unit        |             |                                                                                                                |    |     |      |      |    |      |      |    |      |      |         |                                   |        |                             |  |
| 30                                           | UCFS 206 C  | 647643                                                                                                         | 83 | 111 | 10,5 | 15,9 | 22 | 44   | 65,8 | 62 | 60   | 50   | Type A  | 0,73                              | 615682 |                             |  |
| 35*                                          | SUCFS 207 C | 647653                                                                                                         | 83 | 111 | 10,5 | 15,9 | 22 | 45,5 | 65,8 | 72 | 70   | 55   | Type A  | 0,84                              | 615692 |                             |  |
| 40*                                          | SUCFS 208 C | 647663                                                                                                         | 83 | 111 | 10,5 | 15,9 | 22 | 47   | 65,8 | 80 | 78   | 65   | Type A  | 0,94                              | 63549  |                             |  |
| Eccentric collar shaft locking • Closed unit |             |                                                                                                                |    |     |      |      |    |      |      |    |      |      |         |                                   |        |                             |  |
| 40*                                          | SHCFS 208 C | 647693                                                                                                         | 83 | 111 | 10,5 | 15,9 | 19 | 51,7 | 65,8 | 80 | 78   | 65   | Type D  | 1,00                              | 63539  |                             |  |
| Eccentric collar shaft locking • Open unit   |             |                                                                                                                |    |     |      |      |    |      |      |    |      |      |         |                                   |        |                             |  |
| 40*                                          | SHCFS 208 C | 647723                                                                                                         | 83 | 111 | 10,5 | 15,9 | 19 | 51,7 | 65,8 | 80 | 78   | 65   | Type D  | 1,00                              | 63549  |                             |  |

\* = Version with special fixing holes.

<sup>1)</sup> = Dimensions Df max / Df min must be respected to ensure positive retention of the seals and to allow air bleeding during lubrication.

Packaging: 4 pieces.