

UCFL/C - SUCFL/C - HCFL/C - SHCFL/C

		Housing material															
dia. d mm	Series	Polyamide PA FV Standard Flange (black) Cover (orange)	Dimensions in mm										Bore in frame ²⁾ Df		Bearing	Weight Kg	Spare parts Cover orange
		Code	e	a	b	s	g	i	z	t	Dg	max.	min.	Code			
Grub screws shaft locking • Closed unit																	
20	UCFL 204 C	69016	90	116	62	11	20	15,2	33,2	46	47	45	40	Type A	0,25	681942	
25	UCFL 205 C	68523	99	130	71	11	22,5	16,8	36,3	49,5	52	50	45	Type A	0,33	681952	
30	UCFL 206 C	68399	117	148	85	11	26	20	42	56	62	60	50	Type A	0,42	63154	
35	UCFL 207 C	648131	130	162	93	11	26	19,5	43	59	72	70	55	Type A	0,65	682022	
40	UCFL 208 C	672411	144	176	102	11	30	22	47	65,5	80	78	65	Type A	0,90	63539	
40*	SUCFL 208 C	697712 ¹⁾	117	148	112	11	26	19	44	62	80	78	65	Type A	0,74	63539	
Grub screws shaft locking • Open unit																	
20	UCFL 204 C	69026	90	116	62	11	20	15,2	33,2	46	47	45	40	Type A	0,25	681962	
25	UCFL 205 C	68533	99	130	71	11	22,5	16,8	36,3	49,5	52	50	45	Type A	0,33	681972	
30	UCFL 206 C	68409	117	148	85	11	26	20	42	56	62	60	50	Type A	0,42	69965	
35	UCFL 207 C	648141	130	162	93	11	26	19,5	43	59	72	70	55	Type A	0,65	682032	
40	UCFL 208 C	672421	144	176	102	11	30	22	47	65,5	80	78	65	Type A	0,90	63549	
40*	SUCFL 208 C	697732 ¹⁾	117	148	112	11	26	19	44	62	80	78	65	Type A	0,74	63549	
Eccentric collar shaft locking • Closed unit																	
40*	SHCFL 208 C	697752 ¹⁾	117	148	112	11	26	19	51,7	68	80	78	65	Type D	0,93	600882	
Eccentric collar shaft locking • Open unit																	
40*	SHCFL 208 C	697772	117	148	112	11	26	19	51,7	68	80	78	65	Type D	0,93	600892	

* = Version with special fixing holes.

SUCFL206C/SHCFL206C: Assembly with cylindrical head screws.

¹⁾ = Solid flange.

²⁾ = Dimensions Df max / Df min must be respected to ensure positive retention of the seals and to allow air bleeding during lubrication.

Packaging: 4 pieces.