

UCFL - SUCFL - HCFL - SHCFL

dia. d mm	Series	Housing material										Bore in frame Df mm	Bearing	Weight Kg	
		Polyamide PA FV Standard Flange (black)	Dimensions in mm												
			Code	e	a	b	s	g	i	h	l				z
Grub screws shaft locking • Version with bearing Type B															
20	UCFL 204	69056	90	116	62	11	20	15,2	12,7	25	33,5	24	Type B	0,25	
25	UCFL 205	68563	99	130	71	11	22,5	16,8	14,3	27,5	36,5	29	Type B	0,31	
30	UCFL 206	68439	117	148	85	11	26	19	15,9	32,5	42,2	34	Type B	0,44	
Grub screws shaft locking • Version with stainless steel bearing Type C															
20	UCFL 204	646542	90	116	62	11	20	15,2	12,7	25	33,5	24	Type C	0,25	
25	UCFL 205	646552	99	130	71	11	22,5	16,8	14,3	27,5	36,6	29	Type C	0,31	
30	UCFL 206	646562	117	148	85	11	26	19	15,9	32,5	42,2	34	Type C	0,44	
Grub screws shaft locking • Version with bearing Type A															
20	UCFL 204	655482	90	116	62	11	20	15,2	-	25	33,2	24	Type A	0,23	
25	UCFL 205	655472	99	130	71	11	22,5	16,8	-	27,5	36,3	29	Type A	0,31	
30	UCFL 206	666412	117	148	85	11	26	20	-	32,5	42	34	Type A	0,39	
40*	SUCFL 208	602193 ¹⁾	117	148	112	11	26	19	-	33	44	44	Type A	0,91	
Eccentric collar shaft locking • Version with bearing Type D															
40*	SHCFL 208	602213 ¹⁾	117	148	112	11	26	19	-	33	51,7	44	Type D	0,91	

* = Version with special fixing holes.

SUCFL/SHCFL: Assembly with cylindrical head screws.

¹⁾ = Solid flange.

Packaging: 4 pieces.